

# The Naylor Band-Seal Range

## Standard Couplings



Used for the majority of applications to connect pipe sizes up to 2000mm outside diameter where resistance to shear loads is required.

Applications include:

- Repair and maintenance of existing pipelines.
- Connections between pipes of different materials or sizes (Bushes may be required in these circumstances).
- Making connections by the insertion of new junctions into an existing pipeline.
- Reconnection of laterals on renovated sewers.
- Introducing rocker or hinge pipes outside manholes or structures.

Min Od	Max Od	Coupling Ref.	Code	Box Qty
100	115	NSC 115	76001	20
105	121	NSC 121	76002	20
110	125	NSC 125	76003	20
120	137	NSC 137	76004	20
125	142	NSC 142	76005	12
130	150	NSC 150	76006	12
140	165	NSC 165	76236	12
150	175	NSC 175	76007	10
160	182	NSC 182	76008	10
175	200	NSC 200	76009	10
190	215	NSC 215	76010	8
200	225	NSC 225	76011	6
225	250	NSC 250	76012	6
250	275	NSC 275	76013	6
265	290	NSC 290	76014	5
285	310	NSC 310	76015	3
300	320	NSC 320	76016	3
305	335	NSC 335	76017	3
315	345	NSC 345	76018	4
340	365	NSC 365	76019	4
355	385	NSC 385	76020	4
385	412	NSC 412	76021	2
400	425	NSC 425	76022	2
405	430	NSC 430	76023	2
420	445	NSC 445	76024	2
435	465	NSC 465	76025	2
445	475	NSC 475	76026	2
465	495	NSC 495	76027	2
480	510	NSC 510	76028	2
495	525	NSC 525	76029	2
510	540	NSC 540	76030	2
520	550	NSC 550	76238	2
530	560	NSC 560	76031	2
555	580	NSC 580	76032	2
570	600	NSC 600	76033	2
590	620	NSC 620	76237	2
665	690	NSC 690	76034	2
765	790	NSC 790	76035	2

## Typical Connections

<b>NSC 137</b>	100mm	(4") Salt Glazed Ware
	100mm	Vitrified Clay
	100mm	Densleeve
	100mm	Supersleve
	100mm	Pitch Fibre
	100mm	Asbestos Cement

<b>NSC 290</b>	225mm	(9") Salt Glazed Ware
	225mm	Vitrified Clay
	225mm	Densleeve
	225mm	Supersleve
	225mm	Concrete (OD Up To 290)
	250mm	Asbestos Cement
	250mm	Ductile Iron

<b>NSC 200</b>	150mm	(6") Salt Glazed Ware
	150mm	Vitrified Clay
	150mm	Densleeve
	150mm	Supersleve
	150mm	Concrete
	150mm	Asbestos Cement
	150mm	Pitch Fibre
	150mm	Ultra-rib
	200mm	PVC-u

<b>NSC 385</b>	300mm	(12") Salt Glazed Ware
	300mm	Vitrified Clay
	300mm	Densleeve
	300mm	Supersleve
	300mm	Concrete (OD Up To 385)